

AT5101

MR16 12V Led Garden Spike light

- Tempered Glass lens
- Adjustable Head
- Elegant Design
- Suitable for coastal environments



ORDERING INFORMATION

| | |
|--------------------|------------------------------------|
| Order code | 12205 |
| Description | 6W LED IP65 12v Spike Spot - Black |
| Driver Type | Fixed output |
| Item Code | AT5101/BLK/LED |

EFFICIENCIES

Total System Efficiency 78 lm/W

The performance of each component of a luminaire is demonstrated through its efficiencies, which together determine the total system efficiency of the product. The output of the LED chip is first multiplied by the optical and thermal efficiencies to calculate the Luminaire efficiency. However, this calculation does not consider the driver efficiency. To determine the overall efficiency of the system, the Luminaire efficiency must be multiplied by the driver efficiency, which accounts for all losses in the system.

MECHANICAL

| | |
|--------------------------|--------------|
| Adjustability | Adjustable |
| Body Material | Aluminium |
| Product Finish | Powdercoated |
| Fitting Colour | Black |
| IC Rating | Non-IC |
| Installation Type | Inground |
| IP Rating | IP65 |

ELECTRICAL

| | |
|---------------------------|--------------|
| Electrical Rating | Class III |
| Input voltage | 12Vdc |
| Maximum Wattage | 6 W |
| Switch Type | Inline |
| System Max Wattage | 6 W |
| Working Temp Range | -20 to 40 °C |

LAMP

| | |
|-------------------------------------|--------|
| Beam Angle | 38 ° |
| CCT Configuration | Single |
| Colour Rendering Index (CRI) | >80 |
| Globe Base | MR16 |
| Globe Included | Yes |
| Maximum Bulb Wattage | 6 W |
| Number of Lamps | 1 |

COLOUR TEMPERATURE

| | |
|-------------------------|------------|
| CCT | 4000 K |
| CCT Colour | Cool White |
| LED Wattage | 6 W |
| Luminaire Lumens | 470 lm |

All photometric data has a tolerance of $\pm 10\%$. Luminaire lumens refers to the exit lumens or delivered lumens from the luminaire.

DRIVER

| | |
|--------------------------|-----------------------|
| Dimmable | No |
| Driver Included | No |
| Integrated Driver | No |
| Driver Type | Fixed output |
| Wiring Type | Flying leads (2 wire) |

COMPLIANCE

| | |
|------------------|------------------------------------|
| Standards | AS/NZS 60598.1 AS/NZS 60598.2.4 |
|------------------|------------------------------------|

WARRANTY

| | |
|------------------------------|---------------------------------|
| Domestic Use Warranty | 3 RTB (Total 3 Years) |
| VIP Warranty | 2 Onsite, 3 RTB (Total 5 Years) |

VIP warranty is available to registered users and is subjected to additional terms and conditions.

DIMENSIONS

| | |
|-----------------------|--------|
| Product Height | 347 mm |
| Product Length | 63 mm |
| Product Width | 63 mm |

LINE DRAWINGS

AT5101/BLK/LED

