



50 Metre Rolls

- LED flexible strip light 50m roll
- Dimmable
- Peel and stick backing for initial placement
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003, HV9705-1603 or HV9705-2003)
- Supplied with 25x easy connect tails

3000K

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|------------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9723-IP20-60-3K-50M | 3528 | IP20 | 60 | 390lm | 12v DC | 4.8w/m | 5m | 50mm | 8x2mm |
| | HV9723-IP20-120-3K-50M | 3528 | IP20 | 120 | 780lm | 12v DC | 9.6w/m | 5m | 25mm | 8x2mm |

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

4000K

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|------------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9723-IP20-60-4K-50M | 3528 | IP20 | 60 | 410lm | 12v DC | 4.8w/m | 5m | 50mm | 8x2mm |
| | HV9723-IP20-120-4K-50M | 3528 | IP20 | 120 | 820lm | 12v DC | 9.6w/m | 5m | 25mm | 8x2mm |

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

5500K

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|------------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9723-IP20-60-5K-50M | 3528 | IP20 | 60 | 430lm | 12v DC | 4.8w/m | 5m | 50mm | 8x2mm |
| | HV9723-IP20-120-5K-50M | 3528 | IP20 | 120 | 860lm | 12v DC | 9.6w/m | 5m | 25mm | 8x2mm |

WARRANTY VOID IF MAXIMUM CUT LENGTH EXCEEDS 5 METRES

All LED strip must be installed on an aluminium heat dissipating surface



All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336



NEOLITE Flexible LED Strip

- LED flexi neon LED strip light
- Dimmable
- Beam angle 120 degrees
- Supplied with 4x mounting clips per metre

| IMAGE | PART NUMBER | SMD | IP RATING | LED PER METRE | LUMENS PER METRE | VOLTAGE | WATTAGE PER METRE | MAX LENGTH | CUTTING INCREMENT | SIZE WXH |
|-------|-------------------|------|-----------|---------------|------------------|---------|-------------------|------------|-------------------|----------|
| | HV9793-IP67-90-3K | 2835 | IP67 | 90 | 600lm | 12v DC | 7.2w/m | 5m | 33mm | 8x20mm |
| | HV9793-IP67-90-5K | 2835 | IP67 | 90 | 600lm | 12v DC | 7.2w/m | 5m | 33mm | 8x20mm |

OPTIONAL ACCESSORIES

| | | | | | | | | | | |
|--|------------|---|--|--|--|--|--|--|--|--|
| | HV9793-MC | Mounting clip to suit NEOLITE Flexible LED Strip | | | | | | | | |
| | HV9793-ALU | Optional Aluminium Channel to suit HV9793 - Supplied in 1m length only | | | | | | | | |

Custom cut orders available.

All custom cut orders require minimum of 48hrs production time from order confirmation, plus delivery time.

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336