



ECOGEM S9041TC2 - 10W

Dimmable 10 watt LED downlight, with selectable CCT, IP44.

Application

Ideal for any residential or commercial interior space

Design Specifications

- Selectable CCT 3000K / 4200K / 5700K
- Durable Polyamide, reinforced aluminium body profile, white trim
- Trailing edge dimmable LED driver, with flex and plug
- High efficiency LED optics with an opal polycarbonate diffuser
- White surface mount options available, 145hm, x Ø152mm (S9041SM/TC2WH)
- Colour trim options: Black (S9041 BK RING), Silver (S9041 SL RING), Satin Nickel (S9041 SN RING), IC - 4 rated, double insulated



Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9041TC2WH	240	10	850/1000/900	3000/4200/5700	90
	S9041SM/TC2WH	240	10	850/1000/900	3000/4200/5700	90

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	WHITE	92	103	41(H)
YES	80	WHITE		152	145(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the





time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Dimensions





Before selecting a downlight look out for the marks of Compliance and Safety. Starting with the RCM mark, this signals that the product has been tested to all relevant Australian Safety standards, to ensure the product delivers its designed safety performance. In addition and when thermal insulation batts are installed in the ceiling cavity, look out of the IC rating to ensure the product is suitable for such an application.

