



FLEXI STREAMLINE 24V RGB & TUNABLE WHITE 5M KIT FLBP24V5M/RGBTW - 6W/M

Versatile, COB RGB and tunable white LED, 5m strip kit, 6W/m, IP20, strip width 12mm.

Application

Ideal for residential features

Design Specifications

- 5 metre strip kit includes COB strip with self-adhesive tape, plug and play driver
- Beam distribution 140°
- RGB and tunable white selections 2700-6500K (CRI>90 tunable white)
- Dimming, light level, colour and mode selection is via the supplied remote control.
- Heat sink required for system performance, LED channel options refer this section - [LED channel options \(quick link\)](#)
- Cutable every 125mm NOTE: when cutting LED strip kits greater than 50% of the kit length, it is always important to calculate the remaining LED load to reconfirm its compatibility with the existing driver, as driver changes may be required with moderate reduction in loads



Performance

- Dimmable - **YES**
- Dimmer Type - **RGB Controller**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Watts per metre (W/m)	Beam Angle (°)	LEDs Per Metre	Cutting Interval
	FLBP24V5M/RGBTW	240	6	140	560	125



Body Colour	Dim (mm)
RGBTW	5000(L) x 12(W) x 2(H)

RGB WAVELENGTHS R:620-625, G:515-520, B:465-470nm, TUNABLE WHITE 2700-6500K

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

TO TURN YOUR HOME INTO A **PIXIE SMART HOME**, SELECT A **PIXIE CERTIFIED INSTALLER**.



SIMPLE!

For more
information
please
scan me

