



## PLUTO DIM 700 DC/NR

Australian approved dimmable constant current LED driver with selectable Power and CCT

### Application

The perfect choice for constant current electronic lighting circuits

### Design Specifications

- Compact design, SELV, electrical class II, EMC compliant
- Safe no load, overload, short circuit protection
- Onboard selectable output current (500/700mA)
- Onboard selectable colour temperature, suitable for SAL S9784 TC range - S9784/306/312/606 TC/DP
- Dimmable with a trailing edge dimmer, delivering flickerCONTROLLED driver performance
- Recommended SAL trailing edge dimmers SDD350UM, SDD400U, SDA450U, SDD350BT, SDA450U/LED



### Performance

Dimmable - **YES**

Dimmer Type - **TRAILING EDGE**

### Technical Specification

Model No.	Input Voltage (V/AC)	Frequency (Hz)	Power (W)	Output Current (mA)	Power Factor	Dim (mm)
DIM700/28DC/NR	240	50	28	700	0.9	180(L) x 45(W) x 30(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

# THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE  
CONTROL WITH  
SFI FLICKER  
CONTROL  
TECHNOLOGY**  
when paired with  
**SAL SFI downlights**



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

