



Cut-out: Ø88mm-90mm

FEATURES

- Die-casting aluminum heatsink+PC replaceable frame achieve cost-down .
- downlight solution with good heat dissipation.
- Flicker free triac dimmable Driver.
- Tri-colour.

Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC30-40V/210mA
Power	10W
Rated Input Current	0.04A
PF value	>0.9
THD	25%
Ingress Protection	IP20
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with DIMMATE driver

Optical Data

LED Brand	ZMO
CRI	Ra > 90
Colour temperature	3000K-4000K-5000K
System luminous efficacy up to	86lm/W

Packaging

Box Dimensions	L120 x W120x H80mm
Box Net Weight	0.259Kg
Box Gross Weight	0.3Kg
Carton Dimensions	L375 x W255 x H430 mm/30 PCS
Carton Net Weight	7.78Kg
Carton Gross Weight	9.5Kg



Lens

CCT	Beam Angle	Lumen	Efficacy	Lumen	Efficacy
3000K	20°	680lm	73lm/W	611lm	66lm/W
	40°	653lm	70lm/W	603lm	65lm/W
	60°	692lm	75lm/W	644lm	69lm/W
4000K	20°	734lm	82lm/W	670lm	75lm/W
	40°	727lm	81lm/W	702lm	75lm/W
	60°	771lm	86lm/W	708lm	79m/W
5000K	20°	750lm	81lm/W	694lm	75lm/W
	40°	734lm	79lm/W	675lm	73lm/W
	60°	786lm	85lm/W	725lm	78lm/W

Reflector

