



BESTRI

LED Tri-CCT Exterior Surface Mounted Up/Down Wall Lights IP65

- Input voltage: 100-240V AC 50/60Hz
- Housing: powder coated aluminium
- Diffuser: clear acrylic
- Back plate: PC
- Tri-CCT (3000K / 4000K / 6500K) in one fitting
- LED chips: 4pcs 5050
- Power factor: 0.9
- CRI: >80
- Beam angle: 208.5° (bottom) / 144° (top)
- Ambient temp: -20 to 40°C
- Not suitable for use with dimmers
- Suitable for 2-way switching
- Suitable for use with PIR or Microwave sensors




BESTRI1



BESTRI2

Height: 174mm
 Width of the TOP: 77mm
 Depth of the TOP: 35mm
 Width of the BOTTOM: 106mm
 Depth of the BOTTOM: 51mm



 30,000hr Lifetime	 IP65 Rated	 3 YEAR Replacement Warranty
--	--	---

Part No.	Description	Lumens			Watt	CRI	Box Weight	Box	Carton QTY
		3000K	4000K	6500K					
BESTRI1	WALL S/M Up/Dn 11W LED TRI Cone Dark Grey	374lm	378lm	322lm	11W	>80	0.5kg	12x6x19cm	1/18
BESTRI2	WALL S/M Up/Dn 11W LED TRI Cone White	374lm	378lm	322lm	11W	>80	0.5kg	12x6x19cm	1/18