Tel: 02 9938 7100 | Fax: 02 9938 7115

Waterproof Quick Connector IP68

• Housing: Nylon + PC

• Conductor: Brass



• Rated Power: CONN005: 24A 450VAC; CONN006-007: 32A 450VAC

Rated connecting capacity: CONN005: 0.5-2.5mm²;
CONN006-007: 0.5-4.0mm²

- CONN005 available cable diameter (Rubber): 8-11mm
- CONN006-007 available cable diameter(Rubber): 4-8mm /8-12mm
- CONN005 Extra 8-11mm Rubbers included in the packet
- CONN006-007 Extra 8-12mm Rubbers included in the packet
- Refer to stripping length: External stripping 25mm; Internal stripping 7mm



CONN005



Sealing Ring





Part No.	Description	Max. Current	IP Rating	Box Size (cm)	Box Weight (kg)	Carton Qty
CONN005	CONNECTOR / 2 Way Cable Extension Quick Connect IP68 W/PROOF BLK 24A 450VAC	24A	IP68	15x15x3	0.1	1/125
CONN006	CONNECTOR / 3 Way T Shape Cable Extension 3Pin Terminal IP68 W/PROOF 32A 450VAC	32A	IP68	18x14x4	0.1	1/125
CONN007	CONNECTOR / 3 Way Y Shape Cable Extension 3Pin Terminal IP68 W/PROOF 32A 450VAC	32A	IP68	18x14x4	0.1	1/125

Sealing Ring

Main Body

Tightening Ring

Main