



Dimmable Flush Diffuser LED Recessed Downlights (115mm cut out)




PRODUCT FEATURES

- Input voltage: 240V AC 50/60Hz
- SMD2835 LED chips, power factor: 0.9 •
- Constant current LED driver included
- SAA 2 pin plug & 1.2m leadwire •
- Dimmable models are available
- Can work with sensor
- Ambient temp: -20 to 40°C
- 5 year domestic & 3 year commercial warranty

RECOMMENDED DIMMERS

Dimmer Brand	Part No.	Min/Max Fittings per Dimmer		
CLA	LYNX	2-8 PCS		
HPM LEGRAND	CAT 400P	2-8 PCS		
CLIPSAL	32E450UDM, 32E450TM	2-8 PCS		





CODE	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIAM (mm)	DEPTH (mm)	CUT OUT (mm)	CARTON QTY
GAL217	12W PA WH FIXED RND D/L 3000K DIMM	3000	1020	12	82	Ø145	31	Ø115	1/20
GAL218	12W PA WH FIXED RND D/L 5000K DIMM	5000	1080	12	82	Ø145	31	Ø115	1/20

UPDATED ON 04.04.2017

Website: www.clalighting.com.au

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au Follow us: facebook.com/CLALighting

CLA LIGHTING