

MR16 EXTERIOR 12V INGROUN UP LIGHTERS (small faceplates)




PRODUCT FEATURES


- Input voltage : 12-25DC / AC
- External Control Gear Required
- Max 20W Halogen Globe
- Globe not included
- Fixed MR16 Lampholder
- Recommended CLA LED globes : MR1601 and MR1602
- Material: 316 Stainless steel, solid copper or solid brass faceplates
- Plastic sleeve included (must be installed)
- Fitting slides into sleeve and remains unattached
- Cable included (L950mm)



Sleeve: OD 70mm



IGMEYC, EYESS



IGMGRSS, SMC, SMSS



IGMEYEC



IGMEYESS



IGMSMC



IGMSMSS



IGMGRSS

IGMEYEC	4mm Tempered Glass. Max load capacity 100Kg
IGMEYESS	4mm Tempered Glass. Max load capacity 100Kg
IGMSMC	4mm Tempered Glass. Max load capacity 600Kg
IGMSMSS	4mm Tempered Glass. Max load capacity 600Kg
IGMGRSS	4mm Tempered Glass. Max load capacity 600Kg

PART NO.	DESCRIPTION	PACKAGING DETAILS			
		COLOUR	WEIGHT (KG)	BOX (CM)	CARTON QTY
IGMGRSS	INGROUND / WALL Grilled MR16 12V SS316 RND	316 Stainless steel clear anodized	0.4	13 x 10 x 10	20
IGMEYEC	INGROUND / WALL EYELID MR16 12V COP RND	Polished copper	0.8	16 x 10 x 10	20
IGMEYESS	INGROUND / WALL EYELID MR16 12V SS316 RND	316 Stainless steel clear anodized	0.7	16 x 10 x 10	20
IGMSMC	INGROUND UPLIGHTER / OPEN WALL MR16 12V COP SM RND	Polished copper	0.4	13 x 10 x 10	20
IGMSMSS	INGROUND UPLIGHTER / OPEN WALL MR16 12V SS316 SM RND	316 Stainless steel clear anodized	0.4	13 x 10 x 10	20

UPDATED ON 17/01/2018

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au

Website: www.clalighting.com.au

Follow us: facebook.com/CLALighting