

Tel: 02 9938 7100 | Fax: 02 9938 7115



NOVACOB01

LED Dimmable with **MAGNETIC CHANGEABLE FACEPLATE** Recessed Downlights


TRI-CCT 3000K 4000K 5700K

- Input voltage range: 220-240V 50/60Hz
- Inbuilt constant current driver included
- Housing: aluminium & plastic
- Faceplate: powder coated aluminium
- Diffuser: PC
- Tri-CCT (3000K/ 4000K/ 5700K) in one fitting
- CCT switch on rear
- LED chip: 1PC COB SMD2835
- Power factor: 0.9
- CRI: ≥80
- Flex & plug: 0.6m
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Not suitable for use with sensors



Tested & Recommended Dimmers:

BRAND	PART NO.	PCS PER DIMMER			
CLA	LYNX				
CLIPSAL	32E450TM	1-10PCS			
НРМ	CAT400T				



drawing



Box Include:

- 1x Downlight (NOVACOB)
- 1x Loose Satin Chrome (NOVADSC) faceplate
- 1x Loose White faceplate






NOVACOB01

NOVADSC

Available faceplates (Sold Separately):

- Matt Black (NOVADBLK)
- Antique Brass (NOVADBR)





NOVADBR

NOVADBLK

PART NO.	DESCRIPTION	LUMENS		WATT		вох	вох	CARTON	
	DESCRIPTION	3000K	4000K	5700K	WATT	CUT OUT	WEIGHT	DIMENSIONS	QTY
NOVACOB01	D/L LED COB FIXED WH+S/C DIMM RND TRI	800LM	950LM	850LM	10W	Ø90mm	0.26kg	12x12x7cm	1/40
NOVADBLK	FACEPLATE TO SUIT NOVADLUX01 & NOVACOB01 MATT BLK OD 112mm								
NOVADBR	FACEPLATE TO SUIT NOVADLUX01 & NOVACOB01 ANTIQUE BRASS OD 112mm								