



T9 CIRCULAR FLUORESCENT GLOBES

- Wattage: 22W, 32W & 40W
- 2 pin comes with integral starter
- Triphosphor powder coated for 20-40% increase in light output and life
- G10q base only
- 4 pins together
- Not suitable for dimming

8,000 HRS **1 YEAR WARRANTY**



| CODE | DESCRIPTION | TECHNICAL DATA | | | | DIMENSIONS | |
|-------------|--------------------------|----------------|------------|-------------|----------|------------|------------|
| | | BASE | KELVIN (K) | LUMENS (LM) | WATT (W) | DIAM (mm) | CARTON QTY |
| CLAFCL22WWW | T9 CIRCULAR FL 22W 3000K | G10Q | 3000 | 1250 | 22 | Ø209 | 1/20 |
| CLAFCL22WCW | T9 CIRCULAR FL 22W 4000K | G10Q | 4000 | 1250 | 22 | Ø209 | 1/20 |
| CLAFCL22WNW | T9 CIRCULAR FL 22W 5000K | G10Q | 5000 | 1250 | 22 | Ø209 | 1/20 |
| CLAFCL22WDL | T9 CIRCULAR FL 22W 6500K | G10Q | 6500 | 1250 | 22 | Ø209 | 1/20 |
| CLAFCL32WWW | T9 CIRCULAR FL 32W 3000K | G10Q | 3000 | 2200 | 32 | Ø307 | 1/20 |
| CLAFCL32WCW | T9 CIRCULAR FL 32W 4000K | G10Q | 4000 | 2200 | 32 | Ø307 | 1/20 |
| CLAFCL32WNW | T9 CIRCULAR FL 32W 5000K | G10Q | 5000 | 2200 | 32 | Ø307 | 1/20 |
| CLAFCL32WDL | T9 CIRCULAR FL 32W 6500K | G10Q | 6500 | 2200 | 32 | Ø307 | 1/20 |
| CLAFCL40WWW | T9 CIRCULAR FL 40W 3000K | G10Q | 3000 | 2850 | 40 | Ø400 | 1/20 |
| CLAFCL40WCW | T9 CIRCULAR FL 40W 4000K | G10Q | 4000 | 2850 | 40 | Ø400 | 1/20 |
| CLAFCL40WNW | T9 CIRCULAR FL 40W 5000K | G10Q | 5000 | 2850 | 40 | Ø400 | 1/20 |
| CLAFCL40WDL | T9 CIRCULAR FL 40W 6500K | G10Q | 6500 | 2850 | 40 | Ø400 | 1/20 |

Brochure updated on 09.12.2016