



UB

SURFACE MOUNTED or RECESSED

OPTION Cabinet Underbench

LED Tri-CCT Round Utility Lights



UB1
(White)




(Can be recessed)



UB2
(Black)



UB3
(Silver)





UB4
(Satin Brass)




UB5
(Brushed Chrome)

- Input voltage: 12V DC Constant Voltage
- External driver with 6-way connector (**UB-DRIVER1** sold separately)
- Housing & mounting plate: aluminium
- Diffuser: frosted PMMA
- Tri-CCT (3000K/ 4000K/ 5000K) in one fitting
- CCT switch on rear
- LED chips: SMD2835
- CRI: 80
- Ambient temp: -20 to 50°C



UB-DRIVER1



UB-JUNCTION1

Part No.	Colour	Lumens			Watt	Cut out	Dimensions	Box Weight	Box Size	Carton QTY
		3000K	4000K	5000K						
UB1	White	200lm	210lm	205lm	3W	Ø57mm	Ø70mm x H16mm	0.15kg	8x8x2cm	1/100
UB2	Black	200lm	210lm	205lm	3W	Ø57mm	Ø70mm x H16mm	0.15kg	8x8x2cm	1/100
UB3	Silver	200lm	210lm	205lm	3W	Ø57mm	Ø70mm x H16mm	0.15kg	8x8x2cm	1/100
UB4	Satin Brass	200lm	210lm	205lm	3W	Ø57mm	Ø70mm x H16mm	0.15kg	8x8x2cm	1/100
UB5	Brushed Chrome	200lm	210lm	205lm	3W	Ø57mm	Ø70mm x H16mm	0.15kg	8x8x2cm	1/100
UB-JUNCTION1	12 Way Junction Box with 30cm Cable for UB Range (LED Cabinet Light)							0.04kg	17x12x2cm	1/1
UB-DRIVER1	Driver 12V DC C/VOLT 24W with 6-Way Connector for UB Range (LED Cabinet Light)							0.12kg	15x9x6cm	1/1

*Can be DIY if uses the **UB-DRIVER1** or Must be installed by a licenced electrician if use separate remote driver options with the **UB-JUNCTION1**.