

## sales@clalighting.com.au

## Tel: 02 9938 7100 | Fax: 02 9938 7115

## **VIGO SERIES**


LED Interior Surface Mounted Wall / Reading Lights with USB Function




## VIGOR

- Input voltage: 220-240V AC 50/60Hz
- Inbuilt constant current LED driver included
- Driver output voltage: 2.5-4V & 12-22V
- Driver input current: 0.1A & 0.11A
- Driver output current: 0.7A & 0.3A
- Power factor: 0.5
- Material: iron & aluminium
- Ambient Temp: -20 to 50°C (The life of the lamp will gradually reduce if used outside these temperature parameters)
- Not suitable for dimming
- Suitable for 2-way switching
- Suitable for use with PIR & Microwave sensors







Back Plate

PART NO.	KELVIN (K)	LUMENS (LM)	Lumious Efficiency (Im/W)	WATT (W)	LEDs	CRI	WEIGHT (Kg)	BOX (cm)	CARTON QTY
VIGOL	3000	900	90	6+3	30pcs 2835 + 1pc 3535	≥80	1.88	38.5x17.5x13.5	1/6
VIGOR	3000	900	90	3+6	1pc 3535 + 30pcs 2835	≥80	1.88	38.5x17.5x13.5	1/6

NOTE: Independent switches on mounting base, 5V 2A USB charger in side of mounting base, shelf for safe support of device being charged, reading light is rotable