
Tel: 02 9938 7100 | Fax: 02 9938 7115

WIGTRI

Exterior LED Tri-CCT Surface Mounted Featured Up/Down Wall Lights 1P65





WIGTRI1 (Dark Grey)

Input voltage: 100-240V AC 50/60Hz
Housing: powder coated aluminium

• Diffuser: clear acrylic

• Back plate: L17mm x W9mm

• LED chips: 8pcs 3030

• Tri-CCT (3000K / 4000K / 6500K) in one fitting

• CCT switch location: inside the fitting

• Power factor: 0.9


• CRI: >80

- 2 stickers included which allow narrowing of beam angle at both or either end
- Beam angle: without sticker is 67.6° and with sticker is 63.6° or 65.1°
- Ambient Temperature: -20 to 40°C
- Suitable for 2-way switching
- Suitable for use with PIR or Microwave sensors










WIGTRI2 (White)





Part No.	Description	Lumens			Watt	Length	Height	Depth	Box	Box	Carton
		3000K	4000K	6500K	vvall	Length	Height	Deptil	Weight	Dimension	QTY
WIGTRI1	WALL S/M Up/Dn 11W LED TRI WEDGE Dark Grey Alt Beam	297LM	351LM	294LM	11W	106mm	200mm	62mm	0.8kg	21x21x7.5cm	1/8
WIGTRI2	WALL S/M Up/Dn 11W LED TRI WEDGE WH Alt Beam	297LM	351LM	294LM	11W	106mm	200mm	62mm	0.8kg	21x21x7.5cm	1/8