

- Tri-colour, dual-power batten.



FEATURES

- Built-in high efficiency SMD chips
- Highly transparent opal polycarbonate diffuser
- CCT selectable via switch
- Multi-power selectable, multi-lumen output selectable (8-IN-1 for 5ft)
- Large 6mm terminal block for easy installation
- Quick install modular design
- 0-10V Dimming

INCLUDES

- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted
- Suspended (suspension kit is required)

APPLICATIONS

- Offices
- Garages
- Stations
- Industrial
- Car parks

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	TRI-COLOUR	Ra	DISTRIBUTION	DIMENSIONS(mm)

Part No.	Order Code	Voltage	Watt.	PF	Color Temp.	Lumens ^[2]	Beam Angle	Lifetime L70B50	Size (L*W*H)mm	Net Weight (kg)
211016D	211016D	220-240V	20-50W	0.9	4000K/5000K/6500K	2700-6000lm	120°	50000h	1500*80*65	2.63

Part No.	Model No.	VEET Status	IPART Status
211016D	YKT8BG2-TC-D-2L150 50W	Pending	Pending

[1] Operating Frequency=50/60Hz;

[2] Multi-power description: 4-IN-1(2ft): 9/12/17/20W; 7-IN-1(4ft): 12/15/22/26/29/32/40W; 8-IN-1(5ft): 20/25/30/34/36/40/45/50W

[3] Operating Temperature:-20 °C~+50 °C ; (0 °C~+40 °C for emergency type) ; [4] 211003D/211004D are made to order

* DALI dimming option available on request