

Features



- Five-Colour
- Low profile
- Edge-lit
- Opal diffuser

Applications

Residential, Hallways, Stairwells,
Porches, Wall & Ceilings, Bathrooms

Warranty

5 years



Product Data

Order Code	Wattage	CCT	Lumen Output	Beam Angle	Size (ØxH)mm	Weight (kg)
181007	13W	3K / 4K / 5K / 5.7K / 6.5K	1300Lm	120°	Ø244x23	0.42
181007BK	13W	3K / 4K / 5K / 5.7K / 6.5K	1300Lm	120°	Ø244x23	0.42
181005	17W	3K / 4K / 5K / 5.7K / 6.5K	1700Lm	120°	Ø294x23	0.71
181005BK	17W	3K / 4K / 5K / 5.7K / 6.5K	1700Lm	120°	Ø294x23	0.71
181006	24W	3K / 4K / 5K / 5.7K / 6.5K	2400Lm	120°	Ø424x23	1.30
181006BK	24W	3K / 4K / 5K / 5.7K / 6.5K	2400Lm	120°	Ø424x23	1.30

[1] Operating temperature: -20°C~+40°C

[2] Voltage: 220-240V

[3] PF: 0.9

[4] Inrush current I_{peak} 0.5 (A), Inrush current Twidth 0.98 (uS)

[5] Earth leakage current <0.7mA

