













Image for illustration purposes only.



5500K Natural White LED Strip Lighting

IP20 (4.8w,7.7w, 9.6w)		↓ 2mm
IP20 (14.4w, 7.2w,24w)		↓ 2mm
IP20 (19.2w)		↓ 2mm
IP20 (32.6w)		↓ 2mm
IP20 (46.0w)		↓ 2mm
IP20 (7.7w)		↓ 2mm
IP54 (4.8w)		↓ 3mm
IP54 (14.4w, 7.2w)		↓ 3mm
IP67 (4.8w)		↓ 4mm
IP67 (14.4w,7.2w)		↓ 4mm














- EcoLamp LED flexible strip light
- Dimmable using Havit LED controllers
- Peel and stick backing for initial placement
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003 or HV9705-1603)

All LED strip must be installed on an aluminium heat dissipating surface



All low voltage products that specify LED or are supplied with a 12v DC LED globe must be used with a suitable LED driver, refer to pages (185 - 206)
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (257 - 258)

5500K Natural White LED Strip Lighting

IMAGE	PART NUMBER	SMD	IP RATING	COLOUR TEMP	OUTPUT	POWER	MAX LENGTH	CUTTING INCREMENT	SIZE WxH
	HV9723-IP20-60-5K	3528	IP20 INDOOR	5500k	390lm per 1m 60 LED per 1m	12v DC 4.8w per 1m	5mtr	50mm	8x2mm
	HV9723-IP20-96SM-5K	335	IP20 INDOOR	5500k	500lm per 1m 96 LED per 1m	12v DC 7.7w per 1m	5mtr	33mm	8x2mm
	HV9723-IP20-120-5K	3528	IP20 INDOOR	5500k	780lm per 1m 120 LED per 1m	12v DC 9.6w per 1m	5mtr	25mm	8x2mm
	HV9723-IP20-240-5K-1	3528	IP20 INDOOR	5500k	1560lm per 1m 240 LED per 1m	24v 19.2w per 1m	5mtr	25mm	8x2mm
	HV9723-IP20-240-5K-2	3528	IP20 INDOOR	5500k	1560lm per 1m 240 LED per 1m	24v 19.2w per 1m	5mtr	50mm	16x2mm
	HV9723-IP54-60-5K	3528	IP54 WATER RESISTANT	5500k	390lm per 1m 60 LED per 1m	12v DC 4.8w per 1m	5mtr	50mm	8x3mm
	HV9723-IP54-120-5K	3528	IP54 WATER RESISTANT	5500k	780lm per 1m 120 LED per 1m	12v DC 9.6w per 1m	5mtr	50mm	8x2mm
	HV9723-IP67-60-5K	3528	IP67 WEATHER PROOF	5500k	390lm per 1m 60 LED per 1m	12v DC 4.8w per 1m	5mtr	50mm	10x4mm
	HV9783-IP20-60-5K	2835	IP20 INDOOR	5500k	1200lm per 1m 60 LED per 1m	12v DC 14.4w per 1m	5mtr	50mm	10x2mm
	HV9783-IP54-60-5K	2835	IP54 WATER RESISTANT	5500k	1200lm per 1m 60 LED per 1m	12v DC 14.4w per 1m	5mtr	50mm	10x3mm
	HV9783-IP67-60-5K	2835	IP67 WEATHER PROOF	5500k	1200lm per 1m 60 LED per 1m	12v DC 14.4w per 1m	5mtr	50mm	12x4mm
	HV9783-IP20-120-5K	2835	IP20 INDOOR	5500k	2400lm per 1m 120 LED per 1m	12v DC 24w per 1m	5mtr	25mm	10x2mm
	HV9783-IP20-168-5K	2835	IP20 INDOOR	5500k	4075lm per 1m 168 LED per 1m	24v 32.6w per 1m	5mtr	40mm	19x2mm
	HV9783-IP20-252-5K	2835	IP20 INDOOR	5500k	4600lm per 1m 252 LED per 1m	24v 46w per 1m	3mtr	28mm	39x2mm

All low voltage products that specify LED or are supplied with a 12v DC LED globe must be used with a suitable LED driver, refer to pages (185 - 206)
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (257 - 258)