


MR16 PLVS SERIES

- 12V AC/DC
- 2700K and 3000K
- Mold Injected High Thermal Plastic+ Aluminium Body (3W, 5W)
- Aluminium Body (7W)
- GU5.3 BASE SOCKET
- 80+ CRI / 90+ CRI14
- 15,000 Hour rated
- (FL) Flood 38 °
- Stainless Steel Pins
- Made for use in Enclosed Fixtures and Damp Location
- Constant Current Driver For Long Life
- Dimmable with Lutron Magnetic Dimmers
 - Dimming may Reduce Life Span
- 2700K and 3000K
- PLVS3-MR16
 - 230 Lumens, 3 Watts
- PLVS5-MR16
 - 350 Lumens, 5 Watts
- PLVS7-MR16
 - 450 Lumens, 7 Watts



PLVS3 3W



PLVS5 5W



PLVS7 7W

| PART NUMBER | Watts | COLOUR TEMP | LUMENS | Beam | INPUT |
|-------------------|-------|-------------|--------|------|-----------|
| PLVS3-MR16-FL-27K | 3W | 2700K | 230 | 38° | 12V AC/DC |
| PLVS3-MR16-FL-30K | 3W | 3000K | 230 | 38° | 12V AC/DC |
| PLVS5-MR16-FL-27K | 5W | 2700K | 350 | 38° | 12V AC/DC |
| PLVS5-MR16-FL-30K | 5W | 3000K | 350 | 38° | 12V AC/DC |
| PLVS7-MR16-FL-27K | 7W | 2700K | 450 | 38° | 12V AC/DC |
| PLVS7-MR16-FL-30K | 7W | 3000K | 450 | 38° | 12V AC/DC |