

Last modification 2023-01-22

MDL-16D-16W-930
9329501052976



MODULE 16-16w w/TWIST-ON SYST 16watt DIMMABLE wIth lead&plug 3000K 1280Lm Ra>92 38d

Overview

Family name	Module
Categories	Downlights
Mounting	Recess
Usage	Indoor Lighting,Trade Selection

Color / Material

Fixture Color	Black
Fixture Material	Aluminium
Diffuser Color	Clear
Diffuser Material	Plastic
Cable Color	Black
Cable Material	PVC

Size

Fixture Diameter (cm)	5.0
Fixture Height (cm)	7.5

Specification

Voltage Input	240V
Wattage (max)	16
Globe Type	LED integrated COB
Globe / Light Source qty	1
Globe / Light Source included	Yes
Lumens	1280
Color Temperature	Warm White
Color Kelvin	3000k
Color Rendering	>92
Dimmable	Yes
Power Factor	>0.95

All representations within this document are subject to copyright. ELECTRICAL INSTALLATIONS MUST BE PERFORMED BY A QUALIFIED ELECTRICAL CONTRACTOR AND INSTALLED IN ACCORDANCE WITH AS/NZS 3000.
NOTE : All images , descriptions and dimensions are indicative. Please check latest version of item detail on Telbix website prior to ordering or installation.

Surge Protection	Yes
Beam Angle (degree)	38
Current Output	350
Insulation class	IC-F
IP rating	IP44
Lead and Plug	Yes
Approvals	RCM
Box Contents	Instruction
Installation Required	Yes (by Licensed Electrician only)
Care Instructions	Do not use strong liquid cleaners,Wipe clean with a dry cloth
Replacement Warranty	*5 Years

Barcode

GTIN 9329501052976

Image -dimensions

