

## AT5004 6W

2 X 6W LED Up/Down exterior wall light with glass

diffuser including LED lamps - GU10

- Discrete installation of sets screws
- Tempered Glass lens
- Elegant Design
- Suitable for coastal environments



### ORDERING INFORMATION

<b>Order code</b>	12576
<b>Description</b>	2 x 6W LED White Up/Down Light
<b>Driver Type</b>	Fixed output
<b>Item Code</b>	AT5004/WHT/LED

### EFFICIENCIES

**Total System Efficiency** 78 lm/W

The performance of each component of a luminaire is demonstrated through its efficiencies, which together determine the total system efficiency of the product. The output of the LED chip is first multiplied by the optical and thermal efficiencies to calculate the Luminaire efficiency. However, this calculation does not consider the driver efficiency. To determine the overall efficiency of the system, the Luminaire efficiency must be multiplied by the driver efficiency, which accounts for all losses in the system.

### MECHANICAL

<b>Adjustability</b>	Fixed
<b>Body Material</b>	Aluminium
<b>Product Finish</b>	Powdercoated
<b>Fitting Colour</b>	White
<b>IC Rating</b>	Non-IC
<b>Installation Type</b>	Wall mount
<b>IP Rating</b>	IP65

### ELECTRICAL

<b>Electrical Rating</b>	Class I
<b>Input Frequency</b>	50 Hz
<b>Input voltage</b>	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
<b>Maximum Wattage</b>	12 W
<b>Switch Type</b>	Inline
<b>System Max Wattage</b>	12 W
<b>Working Temp Range</b>	-10 to 40 °C

### LAMP

<b>Beam Angle</b>	38 °
<b>CCT Configuration</b>	Single
<b>Globe Base</b>	GU10
<b>Globe Included</b>	Yes
<b>Maximum Bulb Wattage</b>	6 W
<b>Number of Lamps</b>	2

### COLOUR TEMPERATURE

<b>CCT</b>	4000 K
<b>CCT Colour</b>	Cool White
<b>LED Wattage</b>	6 W
<b>Luminaire Lumens</b>	940 lm

All photometric data has a tolerance of  $\pm 10\%$ . Luminaire lumens refers to the exit lumens or delivered lumens from the luminaire.

## DRIVER

<b>Dimmable</b>	No
<b>Driver Included</b>	Yes
<b>Integrated Driver</b>	Yes
<b>Driver Type</b>	Fixed output
<b>Wiring Type</b>	Re-wireable terminal block (3 pin)

## COMPLIANCE

<b>Standards</b>	AS/NZS 60598.1 AS/NZS 60598.2.1
------------------	------------------------------------

## WARRANTY

<b>Domestic Use Warranty</b>	3 RTB (Total 3 Years)
<b>VIP Warranty</b>	2 Onsite, 3 RTB (Total 5 Years)

VIP warranty is available to registered users and is subjected to additional terms and conditions.

## DIMENSIONS

<b>Product Height</b>	200 mm
<b>Product Length</b>	85 mm
<b>Product Width</b>	60 mm

## LINE DRAWINGS

### AT5004/WHT/LED

