

AT6021/612/DL

LED Backlit Panel, Low Glare, 4000K

Features

- Easy to install
- LED Driver included
- PC Diffuser

ORDERING INFORMATION

Order code	13367
Description	60W LED Backlit panel 600 x 1200 - Daylight
Driver Power	60 W
Driver Type	Fixed output
Item Code	AT6021/612/DL

MECHANICAL

Adjustability	Fixed
Body Material	Steel
Diffuser Material	Polycarbonate
Product Finish	Powdercoated
Fitting Colour	White
IC Rating	Non-IC
Installation Type	Recessed
IP Rating	IP20

ELECTRICAL

Electrical Rating	Class II
Input Frequency	50 Hz
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage	60 W
Switch Type	Inline
Working Temp Range	-10 to 45 °C

LAMP

Beam Angle	90 °
CCT Configuration	Single
CRI	>80
Number of Lamps	1
UGR	<19

COLOUR TEMPERATURE

CCT	6500 K
CCT Colour	Daylight
System Lumens	5860 lm

All photometric data has a tolerance of $\pm 10\%$.

DRIVER

Dimmable	No
Driver Included	Yes
Integrated Driver	No
Driver Mode	Constant Current
Driver Type	Fixed output
Wiring Type	Re-wireable Flex & Plug (2 pin)

ENERGY SAVINGS SCHEME

Ipert Approval	Yes
REES Approval	Yes
VEU Approval	Yes

COMPLIANCE

Daily Use 12 hrs

The Daily Use is the recommended time required to meet the product's design life. Installations can exceed this time, however the product design life will be reduced proportionally.

Standards AS/NZS 60598.1
AS/NZS 60598.2.2
AS/NZS 61347.1
AS/NZS 61347.2.13
AS CISPR 15

WARRANTY

Commercial Use Warranty 3 RTB (Total 3 Years)

Domestic Use Warranty 3 (Yr) RTB

Operational Lifetime 50000 hrs

VIP Warranty 2 Onsite, 3 RTB (Total 5 Years)

VIP warranty is available to registered users and is subjected to additional terms and conditions.

DIMENSIONS


Product Height 34 mm

Product Length 1195 mm

Product Width 595 mm

LINE DRAWINGS

AT6021/612



PHOTOMETRICS

AT6021/612/DL

