

Alta

High velocity 3-in-1 bathroom heater

- 40W ball bearing motor for superior reliability
- Tri-CCT colour selectable LED panel provides efficient illumination
- Two infrared heat lamps provide instant heat
- IPX2 rated safe for use in damp environments
- 3-year in-home warranty for peace of mind



ORDERING INFORMATION

Order code	14841
Description	2-Light high-velocity bathroom heater & exhaust w/LED panel - white - Tri-cct
Item Code	ALTA/2LT/WH

EFFICIENCIES

Total System	Efficiency	90 lm/W

The performance of each component of a luminaire is demonstrated through its efficiencies, which together determine the total system efficiency of the product. The output of the LED chip is first multiplied by the optical and thermal efficiencies to calculate the Luminaire efficiency. However, this calculation does not consider the driver efficiency. To determine the overall efficiency of the system, the Luminaire efficiency must be multiplied by the driver efficiency, which accounts for all losses in the system.

MECHANICAL

Fitting Colour	White
IC Rating	Do not cover
Installation Type	Recessed
IP Rating	IPx2

ELECTRICAL

Electrical Rating	Class II
Input Frequency	50 Hz
Input voltage	230Vac

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

Working Temp Range	40 °C	

LAMP

CCT Configuration	TRI-CCT
Colour Rendering Index (CRI)	>80

COLOUR TEMPERATURE

10 Watts		
Warm White (3000 K)	810 lm	
Cool White (4000 K)	900 lm	
DayLight (5000 K)	880 lm	

AIR MOVEMENT

Outlet	125 mm
Noise level	47 dB
Motor Wattage	40 W
Motor Type	Ball bearing
Fan Type	Centrifugal
Air extraction	400 m3/hr

1300 438 658 sales@evolt.com.au atomlighting.com.au © 2024 Evolt



HEAT

Heater Type	2x 275W IR Heat Lamp (E27)
-------------	----------------------------

COMPLIANCE

Standards	AS/NZS 60335.1
	AS/NZS 60335.2.80
	AS/NZS 60335.2.30
	AS/NZS 60598.1
	AS/NZS 60598.2.2


WARRANTY

DIMENSIONS

Minimum Ceiling Depth	220 mm
Cutout	435x255 mm
Product Height	253 mm
Product Length	480 mm
Product Width	290 mm

LINE DRAWINGS

ALTA/2LT/WH/1



ALTA/2LT/WH

