

20

Driver 24V Slim Dim 60W Constant Voltage Dimmable LED Driver

Description

DRIVER-24V-SLIM-DIM Series are a range of indoor Slim Linear 5-In-1 Dimmable 24V DC Constant Voltage LED Drivers for use with LED strip lighting, LED profiles and much more. Secondary side short circuit protection. Thermal overload protection, over temperature protection and over voltage protection. Complete with 1M flex and plug. Dimming options: Triac Dimmable, 0-10V, 1-10V, 10W PWM, and Potentiometer. Fully Triac dimmable with suitable dimmers. Indoor use only. Choose from 30W, 60W, and 100W wattages. Parallel wiring. Backed by a 5 Year replacement Warranty.

(**5yr**)

| | | termine to |
|------------------------|-------------|--|
| Specification Features | | A THE AND A THE |
| Input Voltage: | 240V AC | A Contractor Contracto |
| Power (W): | 60W | 2 2 - California |
| Output Voltage: | 24V DC | and a second |
| Output Current: | 2.5A | 414 P33 |
| Dimmable: | Yes | |
| IP rating (IP): | IP20 | 8." |
| Voltage Tolerance: | +-0.5V | • |
| Voltage Regulation: | +-0.5% | |
| Power Factor: | PF>0.96 | |
| Working Temp: | -40~+60°C | |
| Working Humidity: | 20~90%RH | |
| Efficiency: | up to 79% | |
| Weight (g): | 350 | |
| Size (mm): | 300x30x18.5 | |

| Diagra | ms / Additional | Item No. DRIVER-24V-SLIM | VariantWattage2018360W |
|--------|-----------------------------|-----------------------------|------------------------|
| 30mm | 300mm L Input N 292mm | | |
| 18.5mm | | | |

Domus 29–31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.