



EMIT-55-TRIO-AB

Tri-Colour Inground Light - Antique Brass

Description

Introducing the EMIT-55 LED Inground Light Series. The EMIT-55 is a 55mm overall diameter inground light with a cutout of 43mm without cannister, ideal for lighting up features where minimalistic light effects are required. Featuring a 2.5W LED output, with a range of different fascia plates and metalware colour options. Choose from Round Open, Square Open, Eyelid and Halo fascias, as well as the multiway fascias available in 1WAY, 2WAY, 3WAY, and 4WAY. Metalware colour options range from Black, Stainless Steel, Antique Brass and Brushed Brass. Tri-Colour Selectable: Choose from 3000K Warm White, 4000K Neutral White and 5500K White colour temperature options. Functional with 12 and 24V DC Constant Voltage LED Drivers. Optional extra accessories such as narrow to medium Beam Angle Lens as well as Honeycomb, Linear Lens and opal diffuser are also available. Part of a family of different sizes to suit most inground lighting applications. Backed by a 5 Year Replacement Warranty.

Specification Features

Input Voltage:	12/24V DC
Power (W):	2.5W
IP rating (IP):	IP67
IK Rating (IK):	IK10

Lumens	RND OPEN	SQR OPEN	EYELID	1WAY	2WAY	3WAY	4WAY	HALO	RING
3000K	135	135	80	2.5	5.4	4.0	4.4	22	28
4000K	145	145	85	2.5	5.4	4.0	4.4	22	28
5500K	150	150	88	2.5	5.4	4.0	4.4	22	28

LED type:	CREE
CCT:	3000K-4000K-5500K (Switchable)
CRI:	≥90
Beam angle (°):	19° - 36° - 60° (36° Standard)
Dimmable:	No
Lifespan (hrs):	50,000hrs
Cutout (Ø):	Ø43MM Without Cannister Ø48MM With Cannister

Requires 12 or 24V Constant Voltage LED Driver (Wire in Parallel)

Compatible with an AC/DC driver. A Domus DC driver is recommended



RO-AB



SQ-AB



EYELID-AB



HALO-AB



RING-AB



1WAY-AB



2WAY-AB



3WAY-AB



4WAY-AB



Honeycomb (Optional)
Variant: 10173



Opal Diffuser (Optional)
Variant: 10167



Linear Lens (Optional)
Variant: 10168



19° Lens (Optional)
Variant: 10169



60° Lens (Optional)
Variant: 10171



Water Stop Cable Joint

Item No.	Variant									CCT
	RND OPEN	SQR OPEN	EYELID	1WAY	2WAY	3WAY	4WAY	HALO	RING	
EMIT-55-TRIO-AB	10117	10118	10119	10120	10121	10122	10123	10124	10125	TRIO

Diagrams / Additional

