

PANEL-303 Backlit LED Panel Light

















Description

10W LED Panel light. White frame, opal diffuser. These are ideal as a ceiling light for T-BAR ceilings, or by using a plaster recessed frame, ideal for commercial applications, office spaces. Now with TRIO, the added option of changing the colour temperature output of the panel with a dip switch function attached to the cable of the fitting.

The added harmonic filter will minimise and reduce the total harmonic distortion and therefore significantly reduce flicker and any potential strobing effects. Standard LED drivers that are not "flicker-free", may potentially cause health implications and interfere with photo quality using digital cameras and recordings with video cameras. This "flicker-free" feature will remove the rolling band flicker effect seen in recorded videos. Ideal for work and office environments, as well as residential applications.

Specification Features

Input Voltage: 240 V AC Power (W): 10 W IP rating (IP): 20

Lumens (lm): Warm White 3000K - 860lm

Neutral White 4000K - 1000lm

White 5700K - 1100lm

LED type: High efficiency SMD LED

CCT: 3000K - 4000K - 5700K (Switchable)

CRI: ≥80 Dimmable: No

Mounting Type: Recessed into standard grid ceiling or via optional

plaster trim kit for plaster board ceilings or via optional

wire suspended or surface mounted kit.

Lifespan (hrs): 40,000hrs





Diagrams / Additional

	(295mm	→	32mm ↔
295mm				9mm

I. N	V_{ariant}	CCT
Item No.	Wht	
PANEL-303-BLT	17615	TRIO