PrestonLED Coping Light

Name	Preston		
Material	Aluminium		
Material	Aldiffilliant		
Colour	Poly Powder Coated Black		
IP Rating	IP65		
Colour Temp	3000k 4000k 5500k		
IK Rating	IK10		
Installation Type	Wall - Surface Mounted		
Diffuser Type	Frosted Polycarbonate		
Lamp Base	Built in LED		
Max Wattage	2.5w, 5w, 7.5w		
Protection Class	12v DC = 3 (No Earth Required)		
Lamp Expectancy	<30,000hrs		
CRI	CRI>80		
Dimmable	Yes		
Warranty	3 Years Replacement		





Dimensions for HV3297	Dimensions for HV3298	Dimensions for HV3298 Dimensions for HV3299	
102	178 ————————————————————————————————————	305 82 0 0 0 0 0	-16-

Product Ordering

	Image	Part Number	Colour Temp	Lumens	Input Voltage	Beam Angle	Included LED	Barcode
		HV3297T-BLK-12V	3000k 4000k 5500k	140lm 150lm 145lm		100°	TRI Colour Built in 2.5w LED	9350418037138
		HV3298T-BLK-12V		280lm 300lm 290lm	12V DC		TRI Colour Built in 5w LED	9350418037169
_		HV3299T-BLK-12V		420lm 440lm 430lm			TRI Colour Built in 7.5w LED	9350418037190











Optional Havit Compatible Accessories

	Image	Part Number	Description
-		12v DC LED Drivers	See Catalogue or Website for full range of 12v DC LED Drivers
		HV9911	Small IP67 Weatherproof Connector
		HV9912	Medium IP67 Weatherproof Connector
		HV9913	Large IP67 Weatherproof Connector

