



Proline Slim 1200mm LED Pendants



Name	Proline
Material	Aluminium
Colour	Powder Coated Black or White
IP Rating	IP20
Colour Temp	<div style="display: flex; gap: 5px;"> <div style="width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black;"></div> 3000k <div style="width: 10px; height: 10px; background-color: #ADD8E6; border: 1px solid black;"></div> 4000k <div style="width: 10px; height: 10px; background-color: #00CED1; border: 1px solid black;"></div> 5500k </div>
IK Rating	IK05
Cable Length	3500mm Adjustable
Installation Type	Ceiling - Surface Mounted
Diffuser Type	Polycarbonate
Lamp Base	Built in LED
Max Wattage	40w LED
Protection Class	1 (Requires Earth)
Lamp Expectancy	<30,000hrs
CRI	CRI>80
Dimmable	Triac Dimmable
Warranty	3 Years Replacement





Warranty
Terms & Conditions



Website

Product Ordering

Image	Part Number	Colour Temp	Lumens	Input Voltage	Beam Angle	Included LED	Barcode
	HV6005T-BLK	3000k 4000k 5500k	3000lm 3270lm 3440lm	240V AC	120°	TRI Colour 40w Built in LED	9350418037336
	HV6005T-WHT						9350418037343

Dimensions

