# AQUA IP66 V2 LED CEILING FAN



Installation Locations: IP66 certified Indoor, outdoor and coastal locations

# **Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

**Top of canopy cover to lowest point of the fan:** Approximately 345mm

**Ceiling to top side of the blade:** Approximately 260mm

# Motor:

157mm x 10mm DC motor Made with high grade copper windings and silicone steel stator. Bearings are sealed and waterproof to ensure quiet operation and long life.

**Top Canopy & Downrod:** Materials: ABS Polymer & Aluminium

Available Colours: Matt White and Matt Black

# Blades:

Sizes: 1320mm (52") Materials: ABS Polymer & UV stabilised Blade Pitch: 13.5°

Available Blade Colours: Matt White, Matt Black & Koa

**Extra Information:** Introduced into the HPI range in 2022 9Speed remote controller Reversible WiFi adaptable (sold separately) Matt White with Matt White Blade

Standard Canopy Cover: Suitable for flat ceiling

Wall Controller Speed Capacitor Values: N/A

Rotational Diameter: 1320mm (52") blade sweep

LED Light: 18W CCT LED light (dimmable)

Colour Temperatures: 3000K, 4000K and 6000K

Weight Including Packaging: Complete fan: 7kg

Packaging Dimensions (cm): Complete Fan: 69L x 30W x 27H

# Accessories (Supplied separately):

Extension Threaded Down Rod 26mm diameter T-Hook for ceiling roses 240V DC Wall Control Tuya Wifi Module Only Pixie HPI Ceiling Fan Module Only

### Warranty:

2 years in-home warranty on all electric components (control modules, remote control system, lighting and accessory wall control) 3 years standard "in home" warranty 3 years extended warranty on motor only (excluding labour)

# Airflow CMH:

14,286 on High speed (Speed 9)

### **RPM & Watt TBA**

	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6	Speed 7	Speed 8	Speed 9
RPMS									
WATTS									

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au