


Lawn Lite Deck Mount Version

Cat. No. LLDMV



The Lawn Lite Deck Mount version is designed to be mounted into timber decks. The lamp can be directed up to 20 degrees at a bush, tree, or the outside of a building etc. without the need to remove the luminaire from the deck due to the vandal-resistant three stainless steel allen head screw fixing system, which attaches the flange to the body of the luminaire. The 'Flush Fit' lens stops water pooling and depositing dirt on the lens. The luminaire has a solid bronze or 316 stainless steel flange with a powder coated black body.



Ordering Information

Luminaire Type	Flange Option	Body	Accessories
LLDMV - Lawn Lite Deck Mount	BK - Black BZ - Bronze GN - Green STAR - Silver Star WH - White WB - Birch DG - Dark Grey OG - Olive Green RG - Beige PR - Primrose SBZ - Solid Bronze SS - 316 Stainless Steel	Luminaires with a Stainless Steel or Bronze flange have a black body, otherwise body is the same as flange colour.	CJK150 - Cable Joint Kit HCR - Hex Cell Retainer LENSLLF - Frosted Lens For LED options, refer to page 10.4.3 (6 watt) or 10.4.4 (3 watt) or http://hunza.co.nz/l.html

Ordering Example: LLDMV SS - Lawn Lite Deck Mount with 316 Stainless Steel Flange

LENSLLF - Frosted Lens

(Accessories ordered separately)

HUNZA™ PURE OUTDOOR LIGHTING

HUNZA FACTORY
130 Felton Mathew Ave
Glen Innes
Auckland 1072
New Zealand

Ph: 64-9-528 9471
Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
Manufactured in New Zealand.
© 2011 Hunza Holdings Ltd.

Ver 1.4

Luminaire Construction

Body:

Cast from virgin high corrosion resistant CC401 low copper aluminium alloy, with chromate substrate and high UV resistant polyester powder coat.

Body Colour: Black.

Flanges:

The flange is attached to the body by three 316 stainless steel allen head anti vandal screws and is available in either powder coated solid aluminium or CNC machined from one of the following metals:

Solid Bronze - 165mm (6½") bar.

Solid 316 Stainless Steel - 165mm (6½") rod.

Mounting

Deck mount version for mounting through a 145mm (5½") hole in a wooden or concrete deck.

The Lawn Lite Deck Mount is not suitable for driving over.

Features

Lens:

12mm (½") 'Flush Fit' clear tempered shatter resistant glass.

Lifetime Warranty.

Gasket:

Nytrol 220°C (428°F).

Lamp Holder:

GU5.3 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) teflon cables. Lamp holder can be rotated 360° and angled up to 20°.

Accessories:

Cable Joint Kit (Cat. CJK150).
Not approved for USA/Canada.
Frosted Lens (Cat. LENSLLF).
Hex Cell Retainer (Cat. HCR).

Standards

Ip67



UL1838

Luminaire Weight

BRZ 1.220kg (2lbs 11oz)
SS 1.510kg (3lbs 5oz)

Power Supply

HUNZA™ Inground or Wall Mount
Transformer: not included.

USA and Canada:

HUNZA™ Wall Mount Transformer:
not included.

Luminaire: supplied with










MR16 GU5.3 20 or 35 watt
lamp max.

LED - Refer to previous page.

USA and Canada:

MR16 GU5.3 20 watt lamp max.

LED - Refer to previous page.



HUNZA™ PURE
OUTDOOR
LIGHTING

HUNZA FACTORY
130 Felton Mathew Ave
Glen Innes
Auckland 1072
New Zealand

Ph: 64-9-528 9471
Fax: 64-9-528 9361
hunza@hunza.co.nz
www.hunza.co.nz

INTERNATIONAL CONTACTS:
www.hunza.co.nz/contacts.php

Specifications may change without notice.
Manufactured in New Zealand.
© 2011 Hunza Holdings Ltd.

Ver 1.4