



# 15W 220MM TRICOLOUR LED CEILING OYSTER LIGHT

**TLEO34515WD** 

The Eclipse II surface mounted LED ceiling light has been superbly designed to the highest of standards, making it ideal for commercial or residential use. This light features a 15W Tricolour SMD LED light that is encased with a toughened opal acrylic diffuser, providing excellent light distribution.





Energy





Watt / Lumens

IP Weatherproof Rating



Secure Lockable Lens Cover



Efficient

Dimmable to 10% Light




Beam Angle


- Surface mounted LED ceiling light
- Ideal for commercial or residential use
- Provides excellent light distribution using SMD LED technology
- Easy switchable Tricolour LED light
- Easy connect swivel lockable cover to base plate

#### **INCLUDES**

Lamp cover, main body, mount screws, & sealing ring

# **DIMENSIONS**





AVERAGE BEAM ANGLE (50%) : 112.0 DEG

UNIT: cd

— C0/180,112.1 lc:455.4

— C90/270,112.0 ic:455.6





Aust/NZ Approval No. SAA192464





#### **TLEO34515WD**

# 15W 220MM TRICOLOUR LED CEILING OYSTER LIGHT

#### **FEATURES**

- Surface mounted LED ceiling light
- Ideal for commercial or residential use
- Vandal resistant with secure lockable lens cover
- Select either 3000k, 4000k, or 5000k light colour temperature setting
- Toughened opal acrylic diffuser
- IP54 weather resistant
- Dimmable to 10% with a trailing edge dimmer



### **SPECIFICATIONS**

Model name	Eclipse II	
Model number	TLEO34515WD	
Power (wattage)	15W	
Voltage	220v – 240v	
Current (mA)	64mA – 69mA	
Switchable Tricolour lumens	3000k-1120lm 4000k-1350lm 5000k-1250lm	
Colour temperature	3000k / 4000k / 5000k	
LED light beam angle	110°	
Dimmable	To 10% with a trailing edge dimmer	
Product size (mm)	Dia 220mm x 54mm	
Material	Toughened opal acrylic diffuser	
LED type	SMD LED	
CRI	≥80	
Approximate lamp life	25000hrs	
Weather resistance rating	IP54	

# **INSTALLATION**

Installation	By licensed electrician only	
Warranty	2 year replacement warranty*	
* For fruither information regarding regarding transports to the second annulation of the second sec		

enclosed warranty statement. Warranty is void unless installed by a licensed electrician.

#### SHIPPING

Packaging size	228 x 228 x 64mm
Gross weight	7.3kg
Carton qty	10

# **AVAILABLE IN WHITE**



Model	Colour	Barcode
TLEO34515WD	White	9312375506188

