

# IP65 LED WEATHERPROOF BATTEN

## SL9721 KEW



### DIMENSIONS



### CONSTRUCTION

- Rounded shape vandal proof design
- Polycarbonate body & diffuser
- Stainless steel clips & screws
- High efficiency SMD LED chips
- Constant current non-dimmable LED driver fitted
- Variable wattage DIP switch
- 100%, 75% or 50% setting available

### IP RATING

- IP65 weatherproof

### DIMMING OPTION

- Trailing edge dimming
- 1-10V dimming
- Digital dimming (DSI, DALI)

### SENSOR OPTIONS

- Integrated microwave motion sensor
- Integrated microwave motion sensor with standBY function



### EMERGENCY OPTIONS

- Compliant to AS2293
- Emergency classification:  
D32@C0, D20@C90 (SL 9721/35EM)  
D50@C0, D25@C90 (SL9721/20EM)



### ACCESSORIES INCLUDED

- Allen key & screws
- PVC cable glands
- Suspension brackets

### INSTALLATION TYPE

- Surface mounted
- Suspended (Suspension kit is required)

### SURFACE/SUSPENDED MOUNTING CLIPS TO MAINTAIN IP RATING



Variable wattage  
DIP switch



Stainless steel clips can be fastened  
with extra locking screws for security



Surface mounting bracket



Suspension bracket



Model No.	Input	Power	Lumen	CCT	Beam Angle	CRI	Dimensions L x W x H
SL9721/20W WW	240V	10/15/20W	900/1350/1800lm	3000K	100°	>80	610 x 115 x 75
SL9721/20W DL	240V	10/15/20W	900/1350/1800lm	5000K	100°	>80	610 x 115 x 75
SL9721/35W WW	240V	18/27/35W	1800/2700/3600lm	3000K	100°	>80	1210 x 115 x 75
SL9721/35W DL	240V	18/27/35W	1800/2700/3600lm	5000K	100°	>80	1210 x 115 x 75

## PHOTOMETRIC DATA

UNIT: cd C0/C180 — C60/240 — C90/270

SL9721/20W WW

SL9721/20W DL

SL9721/35W WW

SL9721/35W DL

