BALMORAL S9087TC - 6W

6 watt dimmable LED downlight with selectable CCT, IP65 ABOVE & BELOW.

Application

Ideal for any retail, residential or commercial interior space

Design Specifications

- Durable polyamide body form
- Stylish white body profile and white trim or black trim and reflector edge models to order
- High performance multi-faceted reflector profile, beam 40°, UGR <19, CRI>90
- Integral, dimmable flickerCONTROLLED LED driver, with flex and plug for easy installation
- Selectable CCT 3000K / 4000K / 5700K
- IC - 4 rated, double insulated, IP65 above and below the ceiling

Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing Edge**

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9087TC/WH	240	6	500/550/550	3000/4000/5700	40
	S9087TC/BK	240	6	500/550/550	3000/4000/5700	40

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	90	WHITE	72	84	55(H)
YES	90	BLACK	72	84	55(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the

NSW/ACT: 02 9723 3099
QLD: 07 3879 5999
VIC/TAS/SA/NT: 03 9532 3168
WA: 08 9248 7458
www.sal.net.au

- 1 -

PDF Prepared: 4.4.2025 6:33pm
Last page update: Apr 2025
© Copyright SAL - All Rights Reserved

time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

S9D97TC 72MM CUT-OUT

S9D93TC 92MM CUT-OUT

S9D93TC 120MM CUT-OUT

NSW/ACT: 02 9723 3099
QLD: 07 3879 5999
VIC/TAS/SA/NT: 03 9532 3168
WA: 08 9248 7458
www.sal.net.au

- 2 -

PDF Prepared: 4.4.2025 6:33pm
Last page update: Apr 2025
© Copyright SAL - All Rights Reserved