



## BALMORAL S9088TC/DP - 6 / 9W

Selectable power 6 / 9 watt dimmable LED downlight with selectable CCT, IP65 ABOVE & BELOW.

### Application

Ideal for any retail, residential or commercial interior space

### Design Specifications

- Durable polyamide body form
- Stylish white body profile and white trim or black trim and reflector edge models to order
- High performance multi-faceted reflector profile, beam 40°, UGR <19, CRI>90
- Integral, dimmable, multi-power flickerCONTROLLED LED driver, with flex and plug for easy installation
- Selectable CCT 3000K / 4000K / 5700K
- IC - 4 rated, double insulated, IP65 above and below the ceiling





### Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing Edge**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)
	<b>S9088TC/DP/WH</b>	240	6/9	750/850/800	3000/4000/5700	40
	<b>S9088TC/DP/BK</b>	240	6/9	700/800/750	3000/4000/5700	40

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	90	WHITE	92	106	67(H)
YES	90	BLACK	92	106	67(H)

Note: Lumens (lm) displayed are at FULL power selection



Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

