





BARRACUDA SL9723TC/MP/EM - 12/40W

MAINTAINED OR NON-MAINTAINED, LED emergency weatherproof batten, 20 or 40 watt models, with selectable CCT and power

Application

Commercial or industrial ceiling or suspended mount applications requiring IP66 and IK10 performance

Design Specifications

- Selectable CCT 3000K /4000K /5700K
- Rounded profile design, robust aluminium body and UV stabilized polycarbonate diffuser
- Integral flickerCONTROLLED non-dimmable, multipower LED driver, 12/15/18/21 watt or 24/30/35/40 watt models
- Secure stainless steel fasteners for the diffuser retention, optional accessories - M6 304 stainless steel security screws to fit a T30 TORX key (SL9723TP/SCREW)
- Installation types Surface mount (standard), Suspended (two off, SSY1512 wire suspension kits are required).
- Compliant to AS/NZS2293 Emergency Lighting & Exit Signs, guaranteed minimum 90 minutes emergency mode function with LiFePO4 battery technology. Emergency spacing class - (20W) D63@C0, D40@C90, (40W) D63@C0, D32@C90.

Performance

• Dimmable - NO









Technical Specification

Product	Model No.	Input Voltage (V/AC)	ССТ (К)	Lumens (lm)	Multiple Wattage	Body Colour
	SL9723/20TC/MP/EM	240	3000/4000/5700	2300/2500/2400	12/15/18/21	GREY
	SL9723/40TC/MP/EM	240	3000/4000/5700	4600/5000/4800	24/30/35/40	GREY
•	SL9723TP/SCREW					M6 304 STAINLESS STEEL
Dim (mm)						

Lumens (Im) shown are displayed at FULL power, for switched lumen values, refer installation instructions

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

137(W)