



BOLLARD SLA7102 - 18W

IP54 18 watt LED bollard

Application

A stylish design, ideal for commercial pathway spaces

Design Specifications

- Die-cast aluminium body
- Durable powder coated black or silver finish
- Clear polycarbonate diffuser
- Matt aluminium reflector
- High efficiency SMD LED chips
- Integral constant current non-dimmable LED driver



Technical Specification


Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Diameter (mm)
SLA7102BK	240	18	1200	6000	75	203
SLA7102SL	240	18	1200	6000	75	203

Model No.	Dim (mm)	Body Colour
SLA7102BK	203(W) x 1000(H)	BLACK
SLA7102SL	203(W) x 1000(H)	SILVER

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".


Dimensions

SLA7102



Photometric Data

Unit: cd C0/C180 — C90/C270 —





Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

**For more
information
please
scan me**

