





BONDI LITE SE7321TC - 4W

IP65 LED architectural wall luminaire, with 4 watt GU10 lamp included

Application

A decorative residential exterior coastal environments or interior spaces

Design Specifications

- Robust reinforced nylon body construction
- Stylish black finish
- Clear tempered glass cover
- Beam distribution 50°, selectable CCT 4 watt GU10 lamp included, CCT 3000 / 4000 / 6000K
- Downward light distribution
- IP65 performance, electrical class II

Performance

• Dimmable - NO

























Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7321TC/BK	240	4	360/400/380	3000/4000/6000	80


Beam Angle (°)	Mass (kg)	Diameter (mm)	Dim (mm)	Base Type	Body Colour
50	0.17	60	119(H) x 120(D)	GU10	BLACK

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions





Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(1) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.