



BRIGHTSTAR ECO SE7199 - 15/50W

IP65 LED multi-purpose floodlight range, IK06 (15-50 watt)

Application

A versatile solution for residential exterior spaces

Design Specifications

- Robust black die-cast aluminium body
- Thre (3) versatile body profiles ranging from 15 - 50 watts, wired with 500mm / 3 x core rubber flex for faster installation
- Durable black powder coated finish
- Tempered glass diffuser
- Beam distribution 110° , CRI 80, 90lm/W performance
- Versatile angled bracket for easy installation



Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7199/15NDL2	240	15	1350	5000	80
	SE7199/30NDL2	240	30	2700	5000	80
	SE7199/50NDL2	240	50	4500	5000	80

Beam Angle (°)	Body Colour	Dim (mm)
110	BLACK	120(W) x 118(H) x 28(D)
110	BLACK	190(W) x 190(H) x 28(D)
110	BLACK	230(W) x 225(H) x 30(D)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".