



COOGEE SE724XL/TC - 10 / 40 W

IP65 LED architectural wall luminaire with combinations of DOWN or UP/DOWN optical distribution

Application

A decorative residential / commercial exterior or interior solution

Design Specifications

- Die-cast aluminium body with a durable black powder coat finish (RAL9005)
- Clear tempered glass cover
- High efficiency LED optics, CRI>80, selectable CCT 3000/4000/5000K
- High performance optical system, standard beam distribution 38° - DOWN or UP/DOWN design options
- Integral non-dimmable LED flickerCONTROLLED gear, with a choice of 10 watt, 2 x 10 watt, 20 watt or 2 x 20 watt models
- Large rectangular mounting base for easy installation



Performance

- Dimmable - **NO**





Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7241L/TC/BK	240	10	1000/1050/1050	3000/4000/5000	80
	SE7242L/TC/BK	240	20	1000/1050/1050	3000/4000/5000	80
	SE7243L/TC/BK	240	20	1950/2050/1850	3000/4000/5000	80
	SE7244L/TC/BK	240	40	1950/2050/1850	3000/4000/5000	80

Beam Angle (°)	Diameter (mm)	Dim (mm)	Body Colour
38	90	175(H) x 135(D)	BLACK
38	90	230(H) x 135(D)	BLACK
38	120	218(H) x 165(D)	BLACK
38	120	300(H) x 165(D)	BLACK

NOTE: Lumens (lm) displayed are per optical head

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

