





### **DALI** 75/120/150


Australian approved, dimmable constant voltage, DALI 2.0 power supply

# **Application**

Reliable constant voltage dimmable driver with DALI 2.0 certified by DiiA

# **Design Specifications**

- Choice of 75 watt / 24V, 150 watt / 24V or 120 watt / 12V
- DALI 2.0 certified by DiiA
- Overload and short circuit protection, DALI and Push DIM control
- SELV and EMC compliant, fixed terminal termination
- flickerCONTROLLED technology
- Electrical class II, Do Not Cover.















## **Performance**

• Dimmable - YES

Dimmer Type - DALI2

# **Technical Specification**

Product	Model No.	Input Voltage (V/AC)	Output Voltage (V/DC)	Power Factor	Power (W)	Dimmable
	DALI75/24FC	240	24	0.95	75	YES
	DALI150/24FC	240	24	0.95	150	YES
	DALI120/12FC	240	12	0.95	120	YES

Dim (mm)
361(L) x 43(W) x 31(H)
361(L) x 43(W) x 31(H)
361(L) x 43(W) x 31(H)

NOTE: Before using the PUSH DIM function, please ensure the driver (L/N supply) is powered ON FIRST, to prevent damage to the PUSH DIM terminations.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all





 $\ensuremath{\mathsf{IP}}$  ratings nominated for Interior products are from "below the ceiling".



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

DIMMABLE CONTROL WITH SFI FLICKER CONTROL TECHNOLOGY when paired with SAL SFI downlights





For related products please scan me





