



DIM 40W/24V

Australian approved IP65 dimmable 24V constant voltage LED driver

Application

Suitable for LED strip, trailing edge dimming models

Design Specifications

- SELV and EMC compliant
- Safe no load operation, 40 watt, minimum load 5 watt, PF > 90, output 24V
- Overload and short circuit protection
- 1.2 m flex & 2 pin plug fitted, output fly leads at the secondary end
- Recommended SAL trailing edge dimmers; SDD350UM, SDD400U, SDA450U, SDD350BT



- IP65
- ta40
- SELV
- 1.2m flex & 2 pin
- 2 YEARS COMMERCIAL WARRANTY
- 3 YEARS RESIDENTIAL WARRANTY

Performance

Dimmable - **YES**
Dimmer Type - **TRAILING EDGE**

Technical Specification

Model No.	Input Voltage (V/AC)	Output Voltage (V/DC)	Power (W)	Power Factor	Dim (mm)
DIM40W/24V	240	24	40	0.9	155(L) x 43(W) x 26(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Wiring Diagram

