



ECOLINE WIDE EMERGENCY SL9738TC/DP2EM - 10/40W


MAINTAINED OR NON-MAINTAINED - Compliant to AS/NZS 2293, wide body batten profile

Application

Perfect for interior commercial emergency lighting installations

Design Specifications

- Wide steel body (110mm) body profile, white powder coat finish
 - LiFePO4 battery technology for long life
 - Designed for both maintained and non maintained system
 - Selectable CCT 3000K/4000K/5700K
 - Selectable maintained power
 - LED charge status display and test switch, guaranteed 90 minutes emergency function
- Emergency classification both models - D50@C0, D32@C90



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SL9738/20TC/DP2EM	240	10/20	2200/2450/2350	3000/4000/5700	80
	SL9738/40TC/DP2EM	240	20/40	4600/5200/4900	3000/4000/5700	80

Body Colour	Dim (mm)	Mass (kg)
WHITE	610(L) x 110(W) x 65(H)	1.22
WHITE	1225(L) x 110(W) x 65(H)	1.93

IMPORTANT NOTES: Lumens (lm) are displayed at full maintained power, (1) Battery warranty twelve (12) months (2) In the interest of transport and safety, emergency products are supplied with the battery disconnected. (3) In addition to specific emergency commissioning instructions, the battery MUST be connected at the time of installation. (4) Continual use in emergency mode greater than 240 hours without recharge, will result in battery failure and void battery warranty.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the



time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".