



ECOLINE WIDE SL9738 TC/DP2 - 10/40W

LED wide body diffused batten with selectable CCT and Dual Power

Application

Conventional style (wide) linear LED batten products for commercial service spaces

Design Specifications

- 110 mm WIDE steel body
- White powder coat finish with PC diffuser
- Large terminal block, easy installation
- Selectable CCT 3000K/4000K/5700K
- High efficiency LED, CRI >80, 120° beam distribution
- Integral constant current non-dimmable LED driver with selectable power, emergency options available, non-dimmable corridorSTANDBY options



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **trailing edge, 1-10V, DALI/DSI**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SL9738/20TC/DP2	240	10/20	2200/2450/2350	3000/4000/5700	80
	SL9738/40TC/DP2	240	20/40	4600/5200/4900	3000/4000/5700	80

Beam Angle (°)	Dimmable	Dim (mm)	Body Colour	IPART
120	OPTIONAL	610(L) x 110(W) x 65(H)	WHITE	N/A
120	OPTIONAL	1225(L) x 110(W) x 65(H)	WHITE	N/A

NOTE: lumens (lm) shown are at FULL power setting

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all



IP ratings nominated for Interior products are from "below the ceiling".

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

