





ECOSTAR S9045TC - 9W

Dimmable 9 watt LED downlight, with selectable CCT

Application

Ideal for any residential or commercial interior spaces

Design Specifications

- Durable die-cast aluminium body profile
- Stylish white powder coat finish
- High output LED optics with selectable CCT 3000/4000/5700K
- Multi-faceted optical system, standard beam distribution 60 degree, UGR<19
- Remote constant current trailing edge dimmable LED driver, with flex and plug
- IC 4 classification

Performance

- Dimmable YES
- Dimmer Type Trailing edge, optional 1-10V, DALI /
 DSI























Technical Specification

| Product | Model No. | Input Voltage (V/AC) | Power (W) | Lumens (lm) | ССТ (К) | Beam Angle (°) |
|---------|------------|-------------------------|--------------|----------------|----------------|-------------------|
| | S9045TC/WH | 240 | 9 | 800/800/850 | 3000/4000/5700 | 60 |

| Dimmable | CRI | Body Colour | Cut Out (mm) | Diameter (mm) | Dim (mm) |
|----------|-----|-------------|--------------|---------------|---------------|
| YES | 80 | WHITE | 72 | 82 | 82(W) x 64(H) |


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions

S9045





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

