



ETON SE7133TC

IP54, GU10 lamp base architectural wall luminaire, with selectable TC lamp included

Application

A decorative residential exterior or interior solution

Design Specifications

- Die-cast aluminium body and powder coat black or silver body profile
- Clear tempered glass cover
- GU10 lamp base, selectable TC lamp GU10L350TC included, lamp options: GU10L550TC, GU10LR750, GU10LA750
- Downward light distribution only



Technical Specification


Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	Diameter (mm)
SE7133TC/BK	240	4	360/400/380	3000/4000/6000	50	68
SE7133TC/SL	240	4	360/400/380	3000/4000/6000	50	68

Model No.	Dim (mm)	Body Colour
SE7133TC/BK	93(W) x 110(H)	BLACK
SE7133TC/SL	93(W) x 110(H)	SILVER

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions





Why is the IP rating important? In brief, IP (Ingress Protection) ratings are defined in EN 60529 and simply defines the ability of an electrical product to seal and protect against the intrusion of foreign objects and water.

(I) As the first numeral stands for intrusion of a foreign object, where (P) as the second numeral stands for the penetration of moisture.

As a guide IP20 rated products would be seen in interior spaces with no requirement for protection against the elements, where an IP65 product would be found in an exterior application which required substantial protection against the elements.

Need more information on IP ratings? Check out the SAL web FAQ's or speak to your local SAL team member.

**For more
information
please
scan me**

