





# FLEXI STREAMLINE 24V SINGLE COLOUR CRI90 2M KIT, FLP24V2M-6W/M

Versatile IP20, CRI>90, LED single colour white, 2 metre strip kit

#### **Application**

Versatile IP20 LED white colour COB strip kit ideal for residential features

#### **Design Specifications**

- 2 metre strip kit includes COB strip with 3M selfadhesive tape, plug and play driver
- Choice of 3000 / 4000 / 6000K, CRI>90
- Streamline COB LED chip technology, providing a smooth lighting profile
- Non-dimmable driver as standard, optional dimmable driver to order.
- Heat sink required for system performance
- Cuttable every 50mm NOTE: when cutting LED strips, it
  is always important to calculate the remaining LED load
  to reconfirm its compatibility with the existing driver, as
  driver changes may be required with moderate
  reduction in loads



















### **Technical Specification**

Model No.	Input Voltage (V/AC)	Watts per metre (W/m)	Beam Angle (°)	Body Colour	CRI	Luminous Flux Per Meter (lm/m)
FLP24V2M/WW	240	6	115	CLEAR	90	460
FLP24V2M/CW	240	6	115	CLEAR	90	525
FLP24V2M/DL	240	6	115	CLEAR	90	490

## **Technical Specification**

Model No.	LEDs Per Metre	Dim (mm)	Colour Temp. (K)
FLP24V2M/WW	320	2000(L) x 8(W) x 2(H)	3000
FLP24V2M/CW	320	2000(L) x 8(W) x 2(H)	4000
FLP24V2M/DL	320	2000(L) x 8(W) x 2(H)	6000

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





# **Product Images**







