



LEDLINE SLD2000TC/MP - 20W

LED diffused batten 20 watt with selectable power and CCT

Application

Conventional LED linear surface mount batten for commercial service spaces

Design Specifications

- Robust, pressed steel body profile
- White powder coat finish with an opal PMMA diffuser
- High efficiency LED optics, CRI > 80
- Integral flickerCONTROLLED non-dimmable LED driver 20 watt as standard, optional dimming, emergency and sensor functions available.
- Default (maximum) current selection is 500mA, refer installation sheet for optional range selections
- Unique diffuser design allows end to end installation and large terminal block for easy installation



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI / DSI**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SLD2000TC/MP	240	20	2250/2400/2300	3000/4000/5700	80
Beam Angle (°)	Dimmable	Dim (mm)		Body Colour		
110	OPTIONAL	600(L) x 100(W) x 77(H)		WHITE		

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

