





MEMPHIS ROUND SL9719RD - 22W

Vandal resistant, IP65 LED round surface mount luminaire, IK10 rated

Application

A robust solution for industrial and commercial spaces

Design Specifications

- Die-cast aluminium body, designed with multi access 20mm rear or side conduit entry points
- Frosted polycarbonate diffuser, silicon gasket
- Stainless steel allen screws
- High efficiency SMD LED chips
- Integral constant current non-dimmable LED driver, with optional corridorSTANDBY function.
- Product selections compliant to AS/NZS2293
 Emergency Lighting & Exit Signs are located in the exterior emergency section of this catalogue.







Performance

Dimmable - **OPTIONAL**Dimmer Type - **TRAINING EDGE**In Built Sensor - **OPTIONAL**Sensor Type - **MICROWAVE**

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Body Colour
SL9719RD	240	22	1700	4000	80	WHITE
SL9719RD/C	240	22	1700	4000	80	WHITE

Model No.	Dim (mm)
SL9719RD	316(W) x 102(H)
SL9719RD/C	316(W) x 102(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".






Dimensions



Photometric Data



SL9719RD at 4000K







PIXIE AMBIENCE, CHANGE YOUR COLOUR TO MATCH YOUR STYLE.

The innovative PIXIE AMBIENCE SWITCH PLATES have been designed with the end user and installer in mind, allowing you to change the colour face plate as fashion demands.

For more information please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

