



÷ 2 2 ¥ 🖌 🎽 = ·*. 🖒



MINI SPIKE DEZINE (XT) SE7361L/TC/AB - 3W

IP54 LED residential mini spike landscape luminaire, in solid Antique Brass finish, with wired selectable CCT

Application

Decorative accent solution for residential garden spaces

Design Specifications

- Selectable CCT wiring configurations
- 12V AC or DC driver required, refer installation instructions for SAL driver model options
- High efficiency LED optics, tempered glass visor
- Supplied with pre-wired 1500mm rubber flex for faster installation, driver ordered separately
- Adjustable knuckle design, perfect for the garden space, ground spike robust black PC design
- IP54, IK06 protection.

Performance

• Dimmable - NO









Technical Specification

Product	Model No.	Input Voltage (V/AC)	Input Voltage (V/DC)	Power (W)	Lumens (lm)	ССТ (К)
1	SE7361LTC/AB (XT)	12	12	3	200/240/200	3000/4000/6000
CRI 80	Beam Angle (°) ³⁸	Mass (kg) 0.53	Diameter (mm) ³⁴	Dim (Body Colour

6000K

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions



