## 





#### **OPAL DIMM LGS14TCD** - 12W

12 watt dimmable LED SMD GLS style opal lamps, with selectable colour temperature

#### Application

Energy efficient LED lamp solutions

#### **Design Specifications**

- Opal polycarbonate diffuser, beam distribution 200 degree
- Poly covered aluminium body, B22 and E27 lamp bases
- High efficiency SMD LED chips, CRI > 80
- Integral trailing edge dimmable LED driver
- Colour temperature selectable 2700K / 4000K / 6000K
- 1:1 size to traditional GLS / A60 lamp, dimmable, suits most

GLS / A60 lamp fittings, double insulation

#### Performance

Dimmable - **YES** Dimmer Type - **TRAILING EDGE** 





### **Technical Specification**

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	ССТ (К)	CRI	Beam Angle (°)
LGS14TC/B22D	240	12	1300/1400/1350	2700/4000/6000	80	200
LGS14TC/E27D	240	12	1300/1400/1350	2700/4000/6000	80	200
Model No.	Dimmable	Diameter (mm)		Length (mm)		Base Type
LGS14TC/B22D	YES	60		112		B22
LGS14TC/E27D	YES	60		112		E27


**IMPORTANT,** where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.





Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

#### Dimensions







# THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE UNIFIT SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.







For related products please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

© Copyright SAL - All Rights Reserved